

LINOLEUM FLOOR TECHNICAL DATA
(If you need different specifications or characteristics, please contact us, relle team will serve you)

| Characteristics | Standard | Unit | Result |
|-------------------------------------|-----------------------|-----------------|--------------------|
| Type of flooring | EN548 | | Linoleum |
| Backing | | | Jute fabric |
| Performance behaviour | | | |
| Roll width | ISO 24341-EN 426 | m | 2.00 |
| Roll length | ISO 24341-EN 426 | m | 20-31 |
| Over thickness | ISO 24346-EN 428 | mm | 2.0/2.5/3.2 |
| Total weight | ISO 23997-EN430 | kg/m2 | 2.4/2.9/3.8 |
| Cotar fastness | ISO 105-B02 | rating | 6 |
| State electrical charge | EN 1815 | kv | <2 |
| Resistance to staining | EN423 | | pass |
| Safety criteria GB 8624-2006 | | | |
| Flammability | GB 8624-2012 | class | B1 |
| Slip resistance | DIN 51130 | group | R9 |
| VOC | GB18586-2001 | | Pass |
| Heavy metal | EN71-3 | | no contain |
| Non toxic (After bum) | DIN 53436 | | no contain |
| Dynamic coefficient of friction | EN13893 | class | DS |
| Classification | | | |
| Domestic | ISO 10874- EN 685 | class | 23 heavy duty |
| Commercial | ISO 10874- EN 685 | class | 34 very heavy duty |
| Industrial | ISO 10874- EN 685 | class | 42 normal duty |
| Additional property | | | |
| Castor chair ✓ | Underfloor heating ✓ | Anti-bacteria ✓ | |
| Antistatic behaviour ✓ | Chemical resistance ✓ | | |